

Single Turn Servo Mount Hall Effect Sensor in Size 09 (22.2 mm)



FEATURES

- Accurate linearity down to: $\pm 0.5\%$
- All electrical angles available up to: 360° (no dead band)
- Very long life: Greater than 50M cycles
- Non contacting technology: Hall effect
- Model dedicated to high quality applications
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


RoHS
COMPLIANT

QUICK REFERENCE DATA

| | |
|------------------|-------------------------------------|
| Sensor type | ROTATIONAL, single turn hall effect |
| Output type | Wires |
| Market appliance | Professional |
| Dimensions | 7/8" (22.2 mm) |

ELECTRICAL SPECIFICATIONS

| PARAMETER | STANDARD | SPECIAL |
|-----------------------------|---|--|
| Electrical angle | $90^\circ, 180^\circ, 270^\circ, 360^\circ$ | Any other angle upon request |
| Linearity | $\pm 1\%$ | $\pm 0.5\%$ |
| Supply voltage | $5 V_{DC} \pm 10\%$ | Other upon request |
| Supply current | 10 mA typ./16 mA max. | 16 mA for PWM output |
| Output signal | Analog ratiometric 10 % to 90 % of V_{supply} or PWM 1 kHz, 10 % to 90 % duty cycle | Other upon request |
| Over voltage protection | | +20 V_{DC} |
| Reverse voltage protection | | -10 V_{DC} |
| Load resistance recommended | | Min. 1 k Ω for analog output and PWM output |
| Hysteresis static | | 0.2° max. |

MECHANICAL SPECIFICATIONS

| PARAMETER | |
|-------------------|--|
| Mechanical travel | 360° continuous, stops upon request |
| Bearing type | 2 ball bearings |
| Standard | IP 50; other on request |

ORDERING INFORMATION/DESCRIPTION

| 78 SHE | 1 | A | 1 | W | A | 1S16 | XXXX | BO 1 | e1 |
|---|---|--------------------------------|--|-------------------------------------|---|---|-----------------|----------------|-------------|
| MODEL | NUMBER OF CUPS | LINEARITY | ELECTRICAL ANGLE | OUTPUT TYPE | OUTPUT SIGNAL | SHAFT TYPE | SPECIAL REQUEST | PACKAGING | LEAD FINISH |
| | 1: 1 Cup 2: 2 Cups 3: 3 Cups 4: 4 Cups | A: $\pm 1\%$ B: $\pm 0.5\%$ | 1: 90° 2: 180° 3: 270° 4: 360° 9: Other angles | T: Turrets W: Wires Z: Custom | A: Analog CW B: Analog CCW C: PWM CW D: PWM CCW Z: Other output | 0: 6 mm 1: 6.35 mm 2: 3.175 mm 9: Special P: Plain S: Slotted Z: Other type | | Box of 1 piece | |
| Shaft length from mounting face standard: 16 mm | | | | | | | | | |

SAP PART NUMBERING GUIDELINES

| 78 SHE | 4 | B | 9 | T | C | 2P22 | XXXX |
|--------|--------------------------|-----------|------------------|-------------|---------------|------------|-----------------|
| MODEL | NUMBER OF CUPS (Signals) | LINEARITY | ELECTRICAL ANGLE | OUTPUT TYPE | OUTPUT SIGNAL | SHAFT TYPE | SPECIAL REQUEST |
| | | | | | | | |




V_{OUT} ANALOG

| | | |
|-----------------------|-----------|-----------|
| Operating temperature | 85 °C | 125 °C |
| Diagnostic high level | 96 % min. | 96 % min. |
| Diagnostic low level | 2 % max. | 4 % max. |



V_{OUT} PWM



| DIAGNOSTIC MODES | | | |
|---|---|---|--|
| FAILURE | V_{out} ANALOG R_{pull-up} | V_{out} ANALOG R_{pull-down} | V_{out} PWM R_{pull-up} = 1 kΩ V_{pull-up} = V_{supply} = 5 V |
| 1: Broken GND | Diagnostic high area | Diagnostic low area | > 97 % V _{supply} without modulation |
| 2: Broken V _{out} | Diagnostic high area | Diagnostic low area | > 97 % V _{supply} without modulation |
| 3: Broken V _{supply} | Diagnostic high area | Diagnostic low area | > 97 % V _{supply} without modulation |
| Over voltage V _{supply} > 7 V | Diagnostic high area | Diagnostic low area | > 97 % V _{supply} without modulation |
| Under voltage V _{supply} < 2.7 V | Diagnostic high area | Diagnostic low area | > 97 % V _{supply} without modulation |

\times Cut off

| ENVIRONMENTAL SPECIFICATIONS | |
|---|--|
| Vibrations | 20 g from 10 Hz to 2000 Hz, EN 60068-2-6 |
| Shocks | 3 shocks/axis; 50 g half a sine 11 ms, EN 60068-2-7 |
| Operating temperature range | -45 °C; +125 °C |
| Life | > 50M of cycles |
| Rotational speed (max.) | 120 rpm |
| Immunity to radiated electromagnetic disturbances | 200 V/m 150 kHz/1 GHz, IEC 62132-2 part 2 (level A) |
| Immunity to power frequency magnetic field | 200 A/m 50 Hz/60 Hz, EN 61000-4-8 (level A) |
| Radiated electromagnetic emissions | 30 MHz/1 GHz < 30 dBμV/m, EN 61000-6-4 (level A) |
| Electrostatic discharges | Contact discharges: ± 4 kV Air discharges: ± 8 kV, EN 61000-4-2 |
| MATERIALS | |
| Housing | Thermoplastic housing |
| Shaft | Stainless steel |
| Output | 3 turrets or 3 lead wires (AWG 22) |


Note

- Nothing stated herein shall be construed as a guarantee of quality or durability.




DIMENSIONS in millimeters

MODEL 78 SHE ...T (OUTPUT BY TURRETS)




General tolerance: ± 0.5 mm


CW or CCW according to output mode choice




View from shaft side



78 SHE (Redundant: 2 signals)




MODEL 78 SHE ...W (OUTPUT BY WIRES)




General tolerance: ± 0.5 mm


CW or CCW according to output mode choice



View from shaft side



78 SHE (Redundant: 2 signals)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.